

# ENHANCE PRODUCTION INSIGHTS WITH VIDEO

Leverage Factbird® VIEW to Take the guesswork out of your production process.

Quickly and easily identify the root cause of stops by just clicking on the datapoint, and watch the video. You'll get actual video footage of the line at the exact moment to diagnose and fix problems straight away.

# How it works

Factbird® VIEW collects and synchronizes video data images from a network camera. The captured images are instantly transmitted to the Factbird Cloud server, where they are seamlessly integrated with your production data and archived in real-time, providing a comprehensive and up-to-the-minute record of your operations.

Facilitate video historical analysis to understand what led to that significant stop or incident last week. Further support root cause analysis and process improvement.

# Key features



# **Non-intrusive solution**

An end-to-end solution that is retrofitted to seamlessly integrate with existing infrastructure.



# **Effortless Installation**

Installation can be done in under 1 hour, while production continues uninterrupted.



#### Secure data

Advanced encryption and secure network communication ensure maximum protection of your data.

# **Checklist for installation**

- Factbird® VIEW
- USB camera
- Power supply unit

# **Product Specifications**

Æ C€

Factbird View Box	
IP Rating	IP66/IP67
Dimensions (LxWxH)	160 × 80 × 65 mm
Material	Polycarbonate
Gasket Material	Polyurethane
UV Resistance	UL 508
Temperature	0-45°C
Camera connection	USB
Supported cameras	Logitech Webcam
Avg. bitrate	2.4 mbps
Resolution	480 p
Frame rate	30 fps
Connectivity	
Connection types	Ethernet, WiFi
WiFi Protocols	802.11 b/g/n/e/i
Security	WPA/WAP2 PSK, WPS
Frequency band	2.4 GHz
Transmission power	max 31 dBm
Ports & Protocols	80 (TCP) HTTP, 443 (TCP) HTTPS, 53 (UDP) DNS, 123 (UDP) NTP

Power Input	
Input Voltage	5 VDC
Input Current	2 A
Power Supply Unit (Packaged)	
Input Voltage	100-240 VAC
Input Current	0,5 A
Frequency	50-60 Hz
Model	T6259ST
Manufacturer	Stontronics
Plug Type	EU Type
Operating Temperature	0-40°C
IP Rating	No

#### **End of life**

When you wish to dispose the sensor cable, please return it to Factbird ApS for recycling or recycle local according to local laws where the end-of-life takes place.

### **Limitations of liability**

Factbird ApS shall not be responsible for any direct or indirect damages, commercial losses, loss of profit in any way connected with the Factbird Analog.

# Warranty

Factbird ApS's warranty is that the product is free from defects in materials and workmanship for a period of one year from the date of sale by Factbird ApS.